


Geberit PE bend with large leg



Example image



Application purposes

- For building drainage
- For site drainage

Characteristics

- Large radius

- UV-resistant

Technical data

Product material

PE-HD

Art. no.	DN	d, ø	arc	X1	X2	K1	K2	r
379.055.16.1	30	32 mm	90°	10 cm	3 cm	7 cm	– cm	3 cm
360.055.16.1	40	40 mm	90°	15 cm	3 cm	12 cm	– cm	3 cm
361.055.16.1	50	50 mm	90°	18 cm	4 cm	14 cm	– cm	4 cm
363.055.16.1	56	56 mm	90°	21 cm	4 cm	17 cm	– cm	4 cm
364.055.16.1	60	63 mm	90°	21 cm	5 cm	16 cm	– cm	5 cm
365.046.16.1	70	75 mm	45°	9.1 cm	5 cm	6 cm	2 cm	– cm
365.051.16.1	70	75 mm	88.5°	21 cm	11.5 cm	14 cm	0 cm	7 cm
365.055.16.1	70	75 mm	90°	21 cm	7 cm	14 cm	– cm	7 cm
366.055.16.1	90	90 mm	90°	24 cm	9 cm	15 cm	– cm	9 cm
367.030.16.1	100	110 mm	30°	19.5 cm	8.5 cm	15.5 cm	4.5 cm	– cm
367.046.16.1	100	110 mm	45°	14.7 cm	6 cm	11 cm	2.5 cm	– cm
367.055.16.1	100	110 mm	90°	27 cm	10 cm	17 cm	– cm	10 cm
367.015.16.1	100	110 mm	15°	18 cm	7 cm	15.5 cm	4.5 cm	– cm
368.015.16.1	125	125 mm	15°	10.5 cm	7.5 cm	7.5 cm	4.5 cm	– cm
368.030.16.1	125	125 mm	30°	12 cm	9 cm	7.5 cm	4.5 cm	– cm
368.055.16.1	125	125 mm	90°	20 cm	11 cm	9 cm	– cm	11 cm
369.015.16.1	150	160 mm	15°	7.5 cm	7.5 cm	4.5 cm	4.5 cm	– cm
369.030.16.1	150	160 mm	30°	9.5 cm	9.5 cm	4.5 cm	4.5 cm	– cm
369.055.16.1	150	160 mm	90°	20 cm	14 cm	6 cm	– cm	14 cm



- Geberit PE bends with angles 15°, 30°, 45° and 88.5° can be welded on both legs with Geberit electrofusion couplings
- Geberit PE bend with angle 90° can be welded on the long leg with Geberit electrofusion couplings