


Geberit PE reducer, eccentric, long



Example image



Application purposes

- For building drainage
- For site drainage

- UV-resistant

Technical data

Product material

PE-HD

Characteristics

- Eccentric

Art. no.	DN	d, Ø	d1, Ø	A	L	l1	l2	K1	K2
368.584.16.1	125 / 100	125 mm	110 mm	0.7 cm	16 cm	7 cm	6.4 cm	4 cm	3 cm
369.584.16.1	150 / 100	160 mm	110 mm	2.5 cm	28 cm	9.4 cm	6.4 cm	6 cm	3 cm
369.587.16.1	150 / 125	160 mm	125 mm	1.7 cm	24 cm	9.4 cm	8 cm	6 cm	5 cm
370.584.16.5	200 / 100	200 mm	110 mm	4.3 cm	28 cm	11.5 cm	3.7 cm	4 cm	0 cm
370.587.16.5	200 / 125	200 mm	125 mm	3.6 cm	28 cm	11.5 cm	3.7 cm	4 cm	0 cm
370.594.16.5	200 / 150	200 mm	160 mm	2 cm	28 cm	11.9 cm	9.1 cm	4 cm	6 cm
371.596.16.1	250 / 200	250 mm	200 mm	2.5 cm	40.5 cm	15.8 cm	15.7 cm	8 cm	8 cm
372.596.16.1	300 / 200	315 mm	200 mm	5.7 cm	58 cm	16.1 cm	15.7 cm	8 cm	8 cm
372.598.16.1	300 / 250	315 mm	250 mm	3.2 cm	43.5 cm	16.1 cm	15.7 cm	8 cm	8 cm