


Geberit Mapress Stainless Steel coupling



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For saturated steam ≤ 120 °C
- For service water
- For treated water
- For rainwater with a pH value of > 6.0
- For grey and black water with pH value > 6.0
- For extinguishing water (wet)
- For sprinklers (wet)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Stainless Steel for liquid media
- Application overview – Geberit Mapress Stainless Steel for gaseous media

Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | CrNiMo steel 1.4401 (EN 10088)

Art. no.	DN	d, ø	L	Z
32009	65	76.1 mm	14.1 cm	3.5 cm
32010	80	88.9 mm	16.2 cm	4.2 cm
33001	10	12 mm	4.2 cm	0.8 cm
32002	12	15 mm	4.8 cm	0.8 cm
32003	15	18 mm	4.8 cm	0.8 cm
32004	20	22 mm	5 cm	0.8 cm
32005	25	28 mm	5.4 cm	0.8 cm
32006	32	35 mm	6.2 cm	1 cm
32007	40	42 mm	7.1 cm	1.1 cm
32008	50	54 mm	8.3 cm	1.3 cm
32011	100	108 mm	19.4 cm	4.4 cm



- In 2021, the dimensions of the aforementioned articles with dimensions d76.1–108 will be modified. The new dimensions are listed in the overview "Dimensional changes for Geberit Mapress Stainless Steel 2021"