


Geberit Mapress Stainless Steel cap



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ °C}$
- For saturated steam $\leq 120\text{ °C}$
- For service water
- For treated water
- For rainwater with a pH value of > 6.0
- For grey and black water with pH value > 6.0
- For extinguishing water (wet)
- For sprinklers (wet)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding
- For permanent termination of pipe ends
- Application overview – Geberit Mapress Stainless Steel for liquid media
- Application overview – Geberit Mapress Stainless Steel for gaseous media

Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | CrNiMo steel 1.4401 (EN 10088)

Art. no.	DN	d, Ø	L	Z
33219	65	76.1 mm	6 cm	0.7 cm
33220	80	88.9 mm	6.7 cm	0.7 cm
33212	12	15 mm	2.3 cm	0.3 cm
33213	15	18 mm	2.3 cm	0.3 cm
33214	20	22 mm	2.4 cm	0.3 cm
33215	25	28 mm	2.6 cm	0.3 cm
33216	32	35 mm	2.9 cm	0.3 cm
33217	40	42 mm	3.3 cm	0.3 cm
33218	50	54 mm	3.8 cm	0.3 cm
33221	100	108 mm	8.2 cm	0.7 cm