


Geberit Mapress Copper coupling



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

Technical data

Product material	Cu-DHP copper CW024A (EN 1412)
------------------	--------------------------------

Art. no.	DN	d, $\varnothing$	L	Z
62001	10	12 mm	4.2 cm	0.8 cm
62002	12	15 mm	4.8 cm	0.8 cm
62003	15	18 mm	4.8 cm	0.8 cm
62004	20	22 mm	5 cm	0.8 cm
62005	25	28 mm	5.4 cm	0.8 cm
62006	32	35 mm	6.2 cm	1 cm
62007	40	42 mm	7.1 cm	1.1 cm
62008	50	54 mm	8.3 cm	1.3 cm