


## Geberit Mapress Copper T-piece, equal



Example image



### Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water  $\leq 120\text{ °C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

### Characteristics

- Pressing indicator
- Leaky if unpressed up to  $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to  $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from  $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

### Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

| Art. no. | DN | d, $\varnothing$ | L       | L1     | I      | Z      | Z1     |
|----------|----|------------------|---------|--------|--------|--------|--------|
| 61000    | 10 | 12 mm            | 6.2 cm  | 3.1 cm | 3.1 cm | 1.4 cm | 1.4 cm |
| 61002    | 12 | 15 mm            | 6.4 cm  | 3.1 cm | 3.2 cm | 1.2 cm | 1.2 cm |
| 61003    | 15 | 18 mm            | 6.8 cm  | 3.4 cm | 3.4 cm | 1.4 cm | 1.4 cm |
| 61004    | 20 | 22 mm            | 7.4 cm  | 3.7 cm | 3.7 cm | 1.6 cm | 1.6 cm |
| 61005    | 25 | 28 mm            | 8.4 cm  | 4.2 cm | 4.2 cm | 1.9 cm | 1.9 cm |
| 61006    | 32 | 35 mm            | 10 cm   | 5.9 cm | 5 cm   | 2.4 cm | 3.3 cm |
| 61007    | 40 | 42 mm            | 11.4 cm | 6.6 cm | 5.7 cm | 2.7 cm | 3.6 cm |
| 61008    | 50 | 54 mm            | 13.8 cm | 7.8 cm | 6.9 cm | 3.4 cm | 4.3 cm |