


Geberit Mapress Copper T-piece, reduced



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)

- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, $\varnothing$	d1, $\varnothing$	d2, $\varnothing$	L	L1	I	I2	Z	Z1	Z2
61252	12 / 10 / 12	15 mm	12 mm	15 mm	6.4 cm	3.3 cm	3.2 cm	3.2 cm	1.2 cm	1.6 cm	1.2 cm
61104	12 / 20 / 12	15 mm	22 mm	15 mm	7.4 cm	3.4 cm	3.7 cm	3.7 cm	1.7 cm	1.3 cm	1.7 cm
61253	15 / 10 / 15	18 mm	12 mm	18 mm	6.8 cm	3.5 cm	3.4 cm	3.4 cm	1.4 cm	1.8 cm	1.4 cm
61235	15 / 12 / 12	18 mm	15 mm	15 mm	7.4 cm	3.5 cm	3.4 cm	4 cm	1.4 cm	1.5 cm	2 cm
61254	15 / 12 / 15	18 mm	15 mm	18 mm	6.8 cm	3.5 cm	3.4 cm	3.4 cm	1.4 cm	1.5 cm	1.4 cm
61236	15 / 15 / 12	18 mm	18 mm	15 mm	7.4 cm	3.4 cm	3.4 cm	4 cm	1.4 cm	1.4 cm	2 cm
61240	20 / 12 / 12	22 mm	15 mm	15 mm	8 cm	3.8 cm	3.7 cm	4.3 cm	1.6 cm	1.8 cm	2.3 cm
61256	20 / 12 / 20	22 mm	15 mm	22 mm	7.4 cm	3.8 cm	3.7 cm	3.7 cm	1.6 cm	1.8 cm	1.6 cm
61257	20 / 15 / 20	22 mm	18 mm	22 mm	7.4 cm	3.8 cm	3.7 cm	3.7 cm	1.6 cm	1.8 cm	1.6 cm
61242	20 / 20 / 12	22 mm	22 mm	15 mm	7.4 cm	3.7 cm	3.7 cm	4.5 cm	1.6 cm	1.6 cm	2.5 cm
61259	25 / 12 / 25	28 mm	15 mm	28 mm	8.4 cm	4.1 cm	4.2 cm	4.2 cm	1.9 cm	2.1 cm	1.9 cm
61260	25 / 15 / 25	28 mm	18 mm	28 mm	8.4 cm	4.1 cm	4.2 cm	4.2 cm	1.9 cm	2.1 cm	1.9 cm
61261	25 / 20 / 25	28 mm	22 mm	28 mm	8.4 cm	4.1 cm	4.2 cm	4.2 cm	1.9 cm	2 cm	1.9 cm
61212	32 / 12 / 32	35 mm	15 mm	35 mm	10 cm	5.1 cm	5 cm	5 cm	2.4 cm	3.1 cm	2.4 cm
61213	32 / 15 / 32	35 mm	18 mm	35 mm	10 cm	5 cm	5 cm	5 cm	2.4 cm	3 cm	2.4 cm
61214	32 / 20 / 32	35 mm	22 mm	35 mm	10 cm	5.2 cm	5 cm	5 cm	2.4 cm	3.1 cm	2.4 cm
61215	32 / 25 / 32	35 mm	28 mm	35 mm	10 cm	5.5 cm	5 cm	5 cm	2.4 cm	3.2 cm	2.4 cm
61229	40 / 12 / 40	42 mm	15 mm	42 mm	11.4 cm	5.4 cm	5.7 cm	5.7 cm	2.7 cm	3.4 cm	2.7 cm
61217	40 / 15 / 40	42 mm	18 mm	42 mm	11.4 cm	5.4 cm	5.7 cm	5.7 cm	2.7 cm	3.4 cm	2.7 cm
61218	40 / 20 / 40	42 mm	22 mm	42 mm	11.4 cm	5.5 cm	5.7 cm	5.7 cm	2.7 cm	3.4 cm	2.7 cm
61219	40 / 25 / 40	42 mm	28 mm	42 mm	11.4 cm	5.8 cm	5.7 cm	5.7 cm	2.7 cm	3.5 cm	2.7 cm
61220	40 / 32 / 40	42 mm	35 mm	42 mm	11.4 cm	6.2 cm	5.7 cm	5.7 cm	2.7 cm	3.6 cm	2.7 cm
61227	50 / 20 / 50	54 mm	22 mm	54 mm	13.8 cm	6.1 cm	6.9 cm	6.9 cm	3.4 cm	4 cm	3.4 cm
61228	50 / 25 / 50	54 mm	28 mm	54 mm	13.8 cm	6.4 cm	6.9 cm	6.9 cm	3.4 cm	4.1 cm	3.4 cm
61225	50 / 32 / 50	54 mm	35 mm	54 mm	13.8 cm	6.8 cm	6.9 cm	6.9 cm	3.4 cm	4.2 cm	3.4 cm
61226	50 / 40 / 50	54 mm	42 mm	54 mm	13.8 cm	7.2 cm	6.9 cm	6.9 cm	3.4 cm	4.2 cm	3.4 cm