


## Geberit Mapress Copper T-piece with female thread



Example image



### Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

### Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

### Technical data

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	Rp	d1, ø	L	L1	I	I2	Z	Z1	Z2
61352	10 / 15 / 10	12 mm	1/2 "	12 mm	6.8 cm	2.4 cm	3.4 cm	3.4 cm	1.7 cm	1.1 cm	1.7 cm
61354	12 / 15 / 12	15 mm	1/2 "	15 mm	6.8 cm	2.6 cm	3.4 cm	3.4 cm	1.4 cm	1.3 cm	1.4 cm
61355	15	18 mm	1/2 "	18 mm	8.2 cm	2.4 cm	4.1 cm	4.1 cm	2.1 cm	1.1 cm	2.1 cm
61357	20 / 15 / 20	22 mm	1/2 "	22 mm	8.4 cm	2.6 cm	4.2 cm	4.2 cm	2.1 cm	1.3 cm	2.1 cm
61395	20	22 mm	3/4 "	22 mm	9 cm	2.7 cm	4.5 cm	4.5 cm	2.4 cm	1.2 cm	2.4 cm
61359	25 / 15 / 25	28 mm	1/2 "	28 mm	8.8 cm	2.9 cm	4.4 cm	4.4 cm	2.1 cm	1.6 cm	2.1 cm
61360	25 / 20 / 25	28 mm	3/4 "	28 mm	8.4 cm	3.5 cm	4.2 cm	4.2 cm	1.9 cm	2 cm	1.9 cm
61362	32 / 15 / 32	35 mm	1/2 "	35 mm	10 cm	3.5 cm	5 cm	5 cm	2.4 cm	2.2 cm	2.4 cm
61366	40 / 15 / 40	42 mm	1/2 "	42 mm	11.4 cm	3.8 cm	5.7 cm	5.7 cm	2.7 cm	2.5 cm	2.7 cm
61370	50 / 15 / 50	54 mm	1/2 "	54 mm	13.8 cm	4.4 cm	6.9 cm	6.9 cm	3.4 cm	3.1 cm	3.4 cm