


Geberit Mapress Copper adapter with male thread



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54$ mm
- Seal ring made of CIIR, black, up to $\varnothing \leq 54$ mm
- Seal ring made of EPDM, black, from $\varnothing > 54$ mm
- Pressing socket with transparent protection plug

Technical data

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, \varnothing	R	L	H
61701	10	12 mm	3/8 "	3.2 cm	1.5 cm
61745	10 / 15	12 mm	1/2 "	3.6 cm	1.9 cm
61702	12 / 10	15 mm	3/8 "	3.3 cm	1.3 cm
61703	12 / 15	15 mm	1/2 "	3.6 cm	1.6 cm
61714	12 / 20	15 mm	3/4 "	3.8 cm	1.8 cm
61704	15	18 mm	1/2 "	3.7 cm	1.7 cm
61705	15 / 20	18 mm	3/4 "	3.8 cm	1.8 cm
61715	20 / 15	22 mm	1/2 "	3.8 cm	1.7 cm
61707	20	22 mm	3/4 "	3.9 cm	1.8 cm
61716	20 / 25	22 mm	1 "	4.1 cm	2 cm
61717	25 / 20	28 mm	3/4 "	4.2 cm	1.9 cm
61708	25	28 mm	1 "	4.3 cm	2 cm
61718	25 / 32	28 mm	1 1/4 "	4.4 cm	2.1 cm
61719	32 / 25	35 mm	1 "	4.8 cm	2.2 cm
61709	32	35 mm	1 1/4 "	4.9 cm	2.3 cm
61721	40 / 32	42 mm	1 1/4 "	5.8 cm	2.8 cm
61710	40	42 mm	1 1/2 "	5.8 cm	2.8 cm
61711	50	54 mm	2 "	6.3 cm	2.8 cm