


Geberit Mapress Copper adapter with female thread



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	Rp	L	Z
61845	10	12 mm	3/8 "	3.1 cm	0.4 cm
61801	10 / 15	12 mm	1/2 "	3.5 cm	0.5 cm
61846	12 / 10	15 mm	3/8 "	3.3 cm	0.3 cm
61802	12 / 15	15 mm	1/2 "	3.8 cm	0.5 cm
61823	12 / 20	15 mm	3/4 "	3.9 cm	0.4 cm
61803	15	18 mm	1/2 "	3.7 cm	0.4 cm
61804	15 / 20	18 mm	3/4 "	3.9 cm	0.4 cm
61805	20 / 15	22 mm	1/2 "	3.6 cm	0.2 cm
61806	20	22 mm	3/4 "	3.9 cm	0.3 cm
61824	20 / 25	22 mm	1 "	4.3 cm	0.5 cm
61819	25 / 20	28 mm	3/4 "	3.9 cm	0.3 cm
61809	25	28 mm	1 "	4.5 cm	0.5 cm
61825	25 / 32	28 mm	1 1/4 "	4.8 cm	0.6 cm
61820	32 / 25	35 mm	1 "	4.6 cm	0.3 cm
61811	32	35 mm	1 1/4 "	5 cm	0.5 cm
61821	40 / 32	42 mm	1 1/4 "	5.2 cm	0.3 cm
61814	40	42 mm	1 1/2 "	5.4 cm	0.5 cm
61818	50	54 mm	2 "	6.3 cm	0.5 cm