


**Geberit Mapress Copper elbow adapter 90° with male thread**



Example image



**Application purposes**

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)

- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

**Characteristics**

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

**Technical data**

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	R	arc	L	H	Z
63892	10	12 mm	3/8 "	90°	3 cm	2.5 cm	1.3 cm
63893	10 / 15	12 mm	1/2 "	90°	3.2 cm	3.1 cm	1.5 cm
63894	12 / 10	15 mm	3/8 "	90°	3.2 cm	2.7 cm	1.2 cm
63873	12 / 15	15 mm	1/2 "	90°	3.5 cm	3.1 cm	1.5 cm
63884	15	18 mm	1/2 "	90°	3.5 cm	3.4 cm	1.5 cm
63895	15 / 20	18 mm	3/4 "	90°	3.8 cm	3.3 cm	1.8 cm
63885	20	22 mm	3/4 "	90°	4.8 cm	4.4 cm	2.7 cm
63886	25	28 mm	1 "	90°	5.8 cm	5.3 cm	3.5 cm
63887	32	35 mm	1 1/4 "	90°	5.5 cm	4.7 cm	2.9 cm
63888	40	42 mm	1 1/2 "	90°	6.2 cm	5.1 cm	3.2 cm
63889	50	54 mm	2 "	90°	7 cm	6.3 cm	3.5 cm