


Geberit Mapress Copper adapter union with male thread



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed
- Union nut made of brass
- Seal ring made of CIIR, black
- Flat gasket made of EPDM
- Pressing socket with transparent protection plug

Technical data

| | |
|---|-----------------------------|
| Media temperature with flat gasket EPDM | 0–100 °C |
| Product material | Gunmetal (CuSn5Zn5Pb2-C) |

| Art. no. | DN | d, \varnothing | R | G | L | H |
|----------|---------|------------------|---------|---------|--------|--------|
| 65531 | 10 | 12 mm | 3/8 " | 1/2 " | 5.1 cm | 3.4 cm |
| 65540 | 10 / 15 | 12 mm | 1/2 " | 1/2 " | 5.5 cm | 3.8 cm |
| 65532 | 12 / 15 | 15 mm | 1/2 " | 3/4 " | 6.1 cm | 4.1 cm |
| 65541 | 12 / 20 | 15 mm | 3/4 " | 3/4 " | 6.3 cm | 4.3 cm |
| 65533 | 15 | 18 mm | 1/2 " | 3/4 " | 6.1 cm | 4.1 cm |
| 65542 | 15 / 20 | 18 mm | 3/4 " | 3/4 " | 6.3 cm | 4.3 cm |
| 65534 | 20 / 15 | 22 mm | 1/2 " | 1 " | 6.7 cm | 4.6 cm |
| 65543 | 20 | 22 mm | 3/4 " | 1 " | 6.8 cm | 4.7 cm |
| 65544 | 20 / 25 | 22 mm | 1 " | 1 " | 6.9 cm | 4.8 cm |
| 65535 | 25 | 28 mm | 1 " | 1 1/4 " | 7.5 cm | 5.2 cm |
| 65536 | 32 | 35 mm | 1 1/4 " | 1 1/2 " | 8 cm | 5.4 cm |
| 65537 | 40 | 42 mm | 1 1/2 " | 1 3/4 " | 8.5 cm | 5.5 cm |
| 65538 | 50 | 54 mm | 2 " | 2 3/8 " | 9.7 cm | 6.2 cm |